

Clack Mineral Tanks



8"-13" Mineral tanks available in blue, natural or black

MADE IN USA



Certified to NSF/ANSI 61

Clack Mineral Tanks are made to ensure reliable performance for many years. The fiberglass filament winding covers a high performance composite high density polyethylene (HDPE) liner. The design provides a continuous seamless inner liner with a glass filled polypropylene inlet for higher strength and pressure capabilities. Tanks are available from 8" to 13" diameter, 2.5"- 8 NPSM top opening.

FEATURES:

- For water softener/filtrations applications
- Capacities from 6.7-16.0 gallons
- 10 year warranty for 8"-13" vessels

MATERIAL OF CONSTRUCTION:

- Inner liner high density polyethylene
- Threaded inlet glass filled polypropylene

OPERATING PARAMETERS:

- Maximum operating pressure: 150 psi
- Maximum operating temperature: 120°F



Available Sizes

| Tank Size (Inches) | Opening Diameter (Inch/mm) | Quantity per Bulk Pack |
|--------------------|----------------------------|------------------------|
| 8x35* | 2.5/63.5 | 18 |
| 8x40 | 2.5/63.5 | 18 |
| 8x44 | 2.5/63.5 | 18 |
| 9x35* | 2.5/63.5 | 16 |
| 9x40 | 2.5/63.5 | 16 |
| 9x48 | 2.5/63.5 | 16 |
| 10x35* | 2.5/63.5 | 16 |
| 10x40 | 2.5/63.5 | 16 |
| 10x44 | 2.5/63.5 | 16 |
| 10x47 | 2.5/63.5 | 16 |
| 10x54 | 2.5/63.5 | 16 |
| 12 x 48 | 2.5/63.5 | 9 |
| 12 x 52 | 2.5/63.5 | 9 |
| 13 x 54 | 2.5/63.5 | 1 |

*Available with or without base.
All above sizes are made in USA.

CLACK DESIGN PARAMETERS:

- Safety factor: 4:1
- Minimum burst at 600 psi
- Tested to 100,000 cycles / 0-190 psi without leakage

NSF DESIGN PARAMETERS:

- Safety factor: 4:1
- Minimum burst at 600 psi
- Tested to 100,000 cycles / 0-150 psi without leakage